

SENZACASTER®

SETTING THE NEW STANDARD FOR INTERNET BROADCASTING

OUR SERVICES

SenzaCaster® is the first truly plug-and-play solution for transmitting high quality video signals across the internet. Open the box, connect the power, your HD-SDI video with embedded audio and simply plug into an RJ-45 internet connection. That's it!

With our revolutionary DASHBOARD, the entire line of SenzaCaster® products can be remotely managed from anywhere in the world. You no longer need to travel an engineer.

Our managed service model is making signal transmission and distribution easier and a lot less expensive. There are all kinds of live applications...news, interview shows, overflow rooms and video distribution to hotels, restaurants and arenas.

SenzaCaster® is an international product...any broadcast format, any power standard...and it's distance AGNOSTIC. And to boot, it makes streaming to Livestream, Facebook, YouTube or your corporate website INCREDIBLY EASY!!!



VIDEO INPUTS

FORMATS	RESOLUTIONS
HD-SDI/SD-SDI (SMPTE 259M-C, SMPTE 292M, SMPTE 274M, SMPTE 296M, SMPTE 424M, SMPTE 425M)	1920x1080p @ 30, 29.97, 25, 24 Hz 1920x1080i @ 60, 59.94, 50 Hz 1280x720p @ 60, 59.94, 50, 30, 29.97, 25 Hz 720x480p @ 30, 29.97 Hz 720x480i @ 59.94 Hz 720x576p @ 25 Hz 720x576i @ 50 Hz

VIDEO OUTPUTS

FORMATS	RESOLUTIONS
HDMI SD-SDI/SMPTE 259M-C HD-SDI/SMPTE 292M & 296M	1920x1080p @ 30, 29.97, 25, 24 Hz 1920x1080i @ 60, 59.94, 50 Hz 1280x720p @ 60, 59.94, 50, 30, 29.97, 25 Hz 720x480p @ 30, 29.97 Hz 720x480i @ 59.94 Hz 720x576p @ 25 Hz 720x576i @ 50 Hz

IP NETWORK INTERFACES

ETHERNET

10/100/1000 Base-T, auto detect DHCP, Connector: RJ45

POWER SUPPLY

Military Grade Internal Supply 85-264 Volts AC, 47-44 Hz
Protection Class II

AUDIO ENCODING

FORMATS	SDI Embedded Audio
RESOLUTIONS	AAC-LC Stereo 192, 160, 128, 112, 96 kb/s

ENVIRONMENTAL

OPERATING TEMPERATURES	-40° C to +70° C (-40° F to +158° F)
RELATIVE HUMIDITY	5% to 95% (non-condensing)
EMC STANDARDS	FCC part 15 class B and CE MIL-STD810F Certified

PRODUCT

Self contained, autonomous unit providing seamless PLUG & PLAY operation.

PHYSICAL

DIMENSIONS	13-3/8" x 11-5/8" x 6" (34 cm x 29.5 cm x 15.2 cm)
WEIGHT	15 lbs. / 6.8 kg